

PULSAtron Series C Selection Guide

LC _ _ _

MODELS:	\$318.00	02	= 0.25 gph/ 6 gpd (0.9 lph) max pres.: 80 PSI (5.6 BAR)
	318.00	03	= 0.50 gph/ 12 gpd (1.9 lph) max pres.: 80 PSI (5.6 BAR)
	318.00	04	= 1.00 gph/ 24 gpd (3.8 lph) max pres.: 80 PSI (5.6 BAR)
	318.00	54	= 1.25 gph/ 30 gpd (4.7 lph) max pres.: 80 PSI (5.6 BAR)

CONTROLS:	N/C	S	= Manual
	84.00	E	= External Pacing w/ Auto/Manual Switch
	84.00	G	= External Pacing w/ Prime Button
	76.00	P	= Stop Function Option

ELECTRICAL:	N/C	A	= 115 Volt / 50-60Hz
	N/C	1	= 115 Volt / 50-60Hz (without agency approvals)
	19.00	B	= 230 Volt / 50-60Hz / 1ph with 6' (1.8m) 3-wire US Plug
	19.00	2	= 230 Volt / 50-60Hz (without agency approvals)

LIQUID END MATERIALS: Pump Head & Fittings/Seats & O-rings/Balls	N/C	PHC	= GFPPL / Hypalon / Ceramic
	11.00	PTC	= GFPPL / TFE / Ceramic
	N/C	VHC	= PVC / Hypalon / Ceramic
	11.00	VTC	= PVC / TFE / Ceramic
	6.00	VVC	= PVC / Viton / Ceramic

See page 6 for additional liquid end materials.

CONNECTION SIZES:	N/C	1	= Tubing .25" I.D. x .38" O.D. / .25" Ball, 0 - 1.88 GPH
	N/C	A	= Tubing .38" I.D. x .50" O.D. / .25" Ball, 0 - 1.88 GPH
	N/C	J	= Tubing, Suc: .19" I.D. x .31" O.D.; Dis: .25" I.D. x .38" O.D.; .19 Ball; 0 - 1.04 GPH
	METRIC:		
	N/C	P	= 4 x 6mm, .25" Ball, 0 - 3.94 LPH
	N/C	U	= 6 x 10mm, .25" Ball, 0 - 7.10 LPH

See page 7 for additional connection sizes.
All pumps with tubing connections come with the following items except for LMH8, LPH8, LEH8, HV series pumps and pumps >150PSI in PVC: 4' Suction, 4' Return, 8' discharge tubing, footvalve/strainer assy., injection valve and bleed valve.

SUFFIX CODES:	N/C	XXX	= No Additional Options
	101.00	130	= PVDF Tubing
	63.00	500	= Five Function Valve
	146.00	520	= Five Function Degas Valve
	173.00	ITS	= 15 gal. ITS Tank System (see page 11 for information on ITS Tanks)
	N/C	CZXXX	= CE Approval (5 digits used for this suffix code)

See pages 9, 10 & 11 for additional information and specs.

A completed model number should look like 'LC03SA-PTC1-XXX'